

**Appendix E:
Noise Supporting Information**

THIS PAGE INTENTIONALLY LEFT BLANK

On-Site Construction Activity

Receptor: Autumn Oak Dr. Residences

Noise Level Calculation Prior to Implementation of Noise Attenuation Requirements											
No.	Equipment Description	Reference (dBA)	Quantity	Usage factor ^[1]	Distance to Receptor	Ground Effect ^[2]	Shielding (dBA) ^[3]	Calculated (dBA)		Energy	
		50 ft						Lmax	Leq		
1	Excavator	80.7	1	10	50	0	0	80.7	70.7	11748975.55	
2	Backhoe	77.6	1	10	50	0	0	77.6	67.6	5754399.373	
3	Ground Compactor	83.2	1	5	50	0	0	83.2	70.2	10446480.65	
4	Front End Loader	79.1	1	10	50	0	0	79.1	69.1	8128305.162	
5											
6											
7											
8											
9											
10											
								Lmax^[4]	83	Leq	76

Notes:

- [1] Percentage of time activity occurs each hour.
- [2] Assumes acoustically "hard" (i.e., reflective) terrain between project site and receptors.
- [3] Conservatively, no shielding is assumed between the project site and this receptor.
- [4] Calculated Lmax is the loudest value.

THIS PAGE INTENTIONALLY LEFT BLANK