

Residential Lighting

2022 California Energy Code Section 150.0 (k)1- Mandatory Features and Devices

Section 150.0 (k)1.C - Recessed downlight luminaries in ceilings: Note: Luminaires recessed into ceiling shall be UL listed for zero clearance insulation contact, be airtight, be sealed with a gasket or calk, shall not contain screw bases sockets.

Table 150.0-A Classification of High Efficacy Light Sources	
High Efficacy Light Sources Light sources shall comply with one of the columns below	
Light sources in this column other than those installed in ceiling recessed downlight	Light sources in this column shall be certified to the Commission as High Efficacy
luminaires are classified as high efficacy and are not required to comply with Reference Joint Appendix JA8	Light Sources in accordance with Reference Joint Appendix JA8 and be marked as meeting JA8.
 Pin-based linear or compact fluorescent light sources using electronic ballasts. HID light sources including pulse-start metal halide, and High pressure sodium. Ceiling fan light kits subject to federal appliance regulations. Luminaires with hardwired high frequency generator and induction lamp. LED light sources installed outdoors. Inseparable SSL luminaires containing colored light sources that are installed to provide decorative lighting. 	7. All light sources in ceiling recessed downlight luminaires. Note that ceiling recessed downlights shall not have screw bases regardless of lamp type as described in Section 150.0(k)1C. 8. Any light source not otherwise listed in this table.

Updated 1-12-2023

phone: (925) 960-4410 fax: (925) 960-4419

TDD: (925) 960-4104