

Above Ground Pools

Please submit two (2) copies of a drawing giving the following information:

- Label Plans, "Above Ground Pool"
- Indicate distance from property lines to pool (setbacks)
- Show location of pool equipment, and indicate circuit breaker size in amperes.
- Indicate size and type of conduit, and show location.
- Indicate size of conductors in conduit.
- If a deck (over 120 square feet of surface area) is to be constructed, provide structural drawings.
- Show location of any existing 110v receptacles that are within 20 feet of the pool.
 Receptacles are not permitted closer than 10 feet. A GFI receptacle is required between 10-20 feet of the pool. If you currently have a GFI receptacle between 10-20 feet, indicate (E) GFI Receptacle on your plans. If there is not a GFI receptacle between 10-20 feet, indicate how you propose to comply with this requirement.
- Tempered glass is required for glazing less than 5 feet above decking and within 5 feet of the pool deck area. Tempered glass is not required if glass is more than 10 feet from the waters edge.
- If the water capacity above ground pool is over 5,000 gallons, installation instructions must be
 on the job site at time of inspection. If 5,000 gallons or less, installation instructions are not
 required.

Please provide copies of your drawings prepared in pen or photo copies as we do not accept pencil drawings.

phone:

fax:

TDD:

(925) 960-4410

(925) 960-4419

(925) 960-4104

(Updated 1-1-14)